



AIRCRAFT® Low Odor Paint Remover

GAR777, CAR777

Gallon, 5 Gallon



- Starts Working in 10 Minutes
- Lifts Multiple Layers
- Removes acrylics, epoxies, enamels, lacquers, polyurethanes, and most other automotive finishes
- Clings well to vertical surfaces
- Best choice for aluminum surfaces*
- Water Rinsable

FINISH REMOVAL TIPS

1. KLEAN-STRIP® AIRCRAFT® Low Odor Paint Remover begins to work in as little as 10 minutes. Once applied, allow time for the remover to do the work. Let stand until finish is completely blistered or liquefied. The time will vary from 10 to 45 minutes for most finishes.
2. Scratching or abrading the finish will often speed up the stripping action.
3. **Always apply a generous amount of remover. Thickly daubing remover onto the surface, rather than brushing, provides better coverage. Thin coats can dry too quickly for the remover to work effectively.**
4. On particularly tough finishes, and to minimize evaporation, secure a 2 – 3 mil polyethylene film over wet remover. For best results, let the remover stand up to two hours, and if necessary, repeat with a second application.
5. If stripper dries on the surface, scrape loosened portions and reapply as needed.
6. Mask seams and trim openings to prevent bleed-back stripping of new finish.

*Not intended for use on aircraft.





AIRCRAFT® Low Odor Paint Remover

	GAR777/CAR777
Appearance	Thick, orange to yellow opaque paste
Vapor Density	Heavier Than Air
Percent Volatile	95% by weight
Flash Point	No Flash to Boiling
CPSC Flammability Classification	Not a Flammable or Combustible Liquid
Boiling Range	105°F to 300°F
VOC Category	Paint Removers or Strippers
Actual VOC	7.1% 0.72 lb/gal 88 gm/L
Max Vapor Pressure of the VOC	18 mmHg @ 20°C
Storage	Store in a cool place. Prolonged exposure to temps in excess of 90°F may cause can to leak or swell. Do not reuse container. Once opened, remover should be used within 6 months or disposed of properly to avoid can deterioration.
Density	10.2 lb/gal 1226 gm/L
Shelf Life	2 years from date of manufacture, in an unopened container
DOT	Compounds, Cleaning Liquid, NA1760, PGII (Contains Ammonium Hydroxide, Methylene Chloride)
HAPS	Methylene Chloride, Methanol
Coverage	25 – 50 sq. ft. per can

ORDERING INFORMATION

Product	Size	Pack	Lbs	Case Cube	Case Width	Case Depth	Case Height	UPC Code	Pallet Qty
CAR777	5 GL	1	54	N/A	N/A	N/A	N/A	0-30192-77730-5	36 units
GAR777	GL	2	22	.397	7 1/16	8 14/16	11 2/16	0-30192-77725-1	104 cases



©2010 W.M. Barr & Co., Inc.
P.O. Box 1879
Memphis, TN 38101
800.238.2672
www.bulldogsticks.com
www.kleanstripauto.com

