

KEEP OUT OF REACH OF CHILDREN

DANGER

Do not breathe fumes, vapors or mist. Do not swallow or take internally. Cannot be made non-poisonous. Affects central nervous system, cardiovascular system, blood and liver. Contains methylene chloride which has been shown to cause cancer in laboratory animals. Do not get in eyes, on skin, or on clothing. Wear safety glasses and gloves. Do not puncture or incinerate container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Vapors may ignite explosively. Keep away from heat, sparks and flame. Contact with flame or hot surface may produce toxic/corrosive gases. Do not smoke. Extinguish all flames and sources of ignition during use and until all vapors are gone.

Use only with adequate ventilation. Use this product outdoors, if possible. If you must use indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. Where adequate ventilation can not be guaranteed, an appropriate and properly fitted NIOSH approved respirator should be used, but should only be done in accordance with manufacturer's directions for respirator use.

BIX SPRAY-ON STRIPPER COMPONENTS: Methanol 67-56-1, Toluene 108-88-3, Methylene Chloride 75-09-2, Acetone 67-64-1, Propane 74-98-6, Butane 106-97-8, Isobutane 75-28-5N

Product Code #13001

0607



Homax Products, Inc.
P.O. Box 5643 • Bellingham, WA 98227
800-729-9029 • www.homaxproducts.com

BIX[®] **SPRAY-ON** **STRIPPER**

HEAVY DUTY **PAINT, VARNISH** **AND STAIN REMOVER**

FAST ACTING, **EASIER TO USE.**

SAFE FOR USE ON WOOD, METAL
AND MASONRY.

REMOVES ALL PAINTS.

CLINGS TO VERTICAL SURFACES.

EASY WATER WASH.

DANGER! **POISON!**

FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL.
MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED.
HARMFUL IF INHALED OR ABSORBED THROUGH SKIN.
CAUSES EYE BURNS. CAUSES SKIN IRRITATION.
SUSPECT CANCER HAZARD. CONTENTS UNDER PRESSURE.

Read other cautions on side panels.

NET WT 16 oz (454 g)

This product is extremely strong and care must be exercised in its handling. It is harmless to wood, metal, canvas, veneer, glass and glued joints, when used properly. On heavily coated surfaces, several applications may be necessary. Do not use on rubber, asphalt, tile, linoleum, fiberglass, plastic, or other synthetics. Test in an inconspicuous place first to see if results are satisfactory.

DIRECTIONS

1. Shake can well.
2. Spray an even coat of stripper onto the surface
3. Wait 10 minutes and without removing any paint or finish, spray another coat of stripper on top of the first coat.
4. Wait 15-20 minutes.
5. To remove the coating use a plastic scraper to scrape off the dissolved finish. Clean carvings and grooves with a scrub brush. Scrub entire piece with #2 steel wool and water to remove all remaining residue. If another application is necessary, allow wood to dry before applying another coat of stripper.
6. Water wash all residue off the surface prior to drying. For best results, use when temperature ranges from 55°F to 85°F.

FIRST AID

If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. If swallowed, do not induce vomiting. Get medical attention immediately. For skin contact, wash thoroughly with soap and water.

WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING

This product contains a chemical known to the State of California to cause cancer or birth defects or other reproductive harm. NON-PHOTOCHEMICALLY REACTIVE VOC <577 g/l