



# PREP-ALL™ Wax & Grease Remover

**GSW362**  
**ESW362**

**Gallon**  
**13.5oz Aerosol**



*Prep-All™ Wax & Grease Remover* is an effective, fast-acting wax & grease remover for many automotive surfaces. It should be used prior to sanding to prolong the life of sandpaper and again after sanding as a clean-up agent prior to applying top coats. Prep-All™ removes old wax build-up before re-application of new wax to promote an even, mirror-like finish. It is also great for removing silicone and road film.

## ORDERING INFORMATION

Product	Size	Pack	Case Wt	Case Cube	Unit Width	Unit Depth	Unit Height	UPC Code	Pallet Qty
GSW362	GL	4	28	.762	6.63	4.13	10.31	0-30192-36225-9	208 units
ESW362	13.5oz	6	6	.296	0	2.69	9.8	0-30192-36299-0	990 units

\*This product is only intended for use on automotive surfaces.

\*GSW362 is not intended for sale or use in California's South Coast Air Quality Management District (SCAQMD), made up of Los Angeles, Riverside, San Bernadino, and Orange counties.

\*ESW362 is compliant for sale in all of California – please check your local air district usage regulations.





## PREP-ALL™ Wax & Grease Remover

	<b>GSW362</b>	<b>ESW362</b>
<b>Appearance</b>	Clear liquid	Clear liquid
<b>Vapor Density</b>	Heavier Than Air	
<b>Percent Volatile</b>	100% by weight	100% by weight
<b>Flash Point</b>	52°F	As Packaged 132°F, Liquid 52°F
<b>CPSC Flammability Classification</b>	Flammable	Flammable
<b>Boiling Range</b>	190°F - 410°F	-25°F - 410°F
<b>Max VOC</b>	750 g/L	N/A
<b>VOC Content</b>	100%	100%
<b>MIR</b>	1.33	1.25
<b>Max Vapor Pressure</b>	11.5	32
<b>Storage</b>	Store in a cool place away from heat, sparks, open flames and all other sources of ignition.	Replace overcap on container after each use. Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.
<b>Density</b>	6.25 lb/gal	N/A
<b>Shelf Life</b>	2 years from date of manufacture, in an unopened container	
<b>DOT</b>	UN1993, Flammable Liquid, N.O.S., 3, PG II (Petroleum Aliphatic Hydrocarbons)	UN1950, Aerosols, flammable, 2.1, Limited Quantity
<b>HAPS</b>	Toluene	Toluene

©2010 W.M. Barr & Co., Inc.  
P.O. Box 1879  
Memphis, TN 38101  
800.238.2672  
[www.bulldogsticks.com](http://www.bulldogsticks.com)  
[www.kleanstripauto.com](http://www.kleanstripauto.com)

